

Monocouche NMS Paint

Specialised application for scraped render finishes

A high performance mineral paint

- A high quality mineral paint for new build masonry substrates
- A low-maintenance finish on to external wall insulation
- Rejuvenates existing rendered substrates



Colours

Monocouche NMS Paint is available in a wide range of colours. Specifiers should consult colour chart available from Monocouche LTD

Final colour selection must be made against an actual sample. Monocouche Ltd will not accept responsibility for colours chosen from any source other than an actual sample.

Colour samples are freely and readily available from Monocouche Ltd.

Preparation

Existing rendered substrates

Hammer test and remove all areas of loose, flaked render.

Treat surfaces with antifungal spray.

Wire brush, or wash down surface with a high pressure jet (40 to 80 bar) to remove all traces of growth.

Make good surfaces using render aid.

New rendered substrates

Ensure new render is fully cured, clean, dry and free from dust.

Application

Note:

To ensure colour consistency, paint required for complete and adjoining panels should be of the same batch number or be thoroughly mixed together before use.

When the surface is dry, apply a first coat of **Monocouche NMS Paint**, diluted 10 to 15% with clean water, using a wool roller.

Apply a second, undiluted coat when the first coat is dry, normally between 6 and 24 hours.

Stable surfaces with particularly high suction should be primed.

To ensure product acceptability, colour samples must be requested. These are freely and readily available from Monocouche Ltd.

Spillages stain and are difficult to remove so:

- protect vulnerable areas thoroughly
- wear protective clothing
- clean tools with water

Good practice

Do not apply:

- If frost is forecast within 24 hours of use
- In damp/wet conditions
- In temperatures below 5°C or above 30°C
- On elevations in direct sunlight or where the substrate is hot

Where it has been agreed that painting will be carried out as part of a remedial action to harmonise colour on a rendered facade, complete and all adjoining panels must be over coated. The painting of any panels should be carried out at the same time under the same weather conditions.

Exact colour matching of mineral render and paint is not guaranteed. Colour appearance will vary naturally between paint and render as the products are fundamentally different in composition and hence finished appearance.

Storage and Shelf life

Wet pre-mixed materials must be stored frost-free and protected from direct sunlight and extreme heat. To prevent ingress of air, buckets should be stacked no more than 2 high, and where a central support is used, to a maximum height of 4. When stored under these conditions, the shelf life of the product is 12 months from the date of manufacture.

Health and Safety

Essentially non-hazardous.

For further information, please request the Material Safety Data Sheet for this product.

Monocouche
Ashpine House, 5 Slaney Court, Dublin Industrial Estate, Glasnevin, Dublin 11

Tel: +353 (0) 1 899 7199

Fax: +353 (0) 1 882 7842

Email: info@monocoucheltd.com

Web: www.monocoucheltd.com

This document is the copyright of Monocouche Ltd. and must not be copied in part or in whole without permission.